

TULEX-HO-120 Dim-to-Red




- Innovative tube light with wide beam angle suitable for pig farms
- Improve animal welfare with natural sunrise/ sunset simulation
- Durable and sustainable lighting solution

Invest in the quality of your lighting system

Made with species-specific technology, the TULEX-HO-120 Dim-to-Red tube durability, high efficiency and more. light features a wide beam angle for even illumination in large spaces. It dims fully to red, which allows for natural sunrise / sunset simulation and helps prevent disturbance in circadian rhythm cycles, in addition to lowering stress markers in animals. The TULEX-HO-120 Dim-to-Red offers optimal

Dimensions



Visit our website for more information: www.once.lighting

Specifications and Ordering

TULEX-HO-120 Dim-to-Red Specifications

Nominal power	21W	
Luminous flux - human photopic	2050 lm	
Luminous flux - poultry photopic	-	
Initial LED luminaire efficacy	97 lm/W	
Input voltage	Input voltage 48VDC	
Input frequency	Input frequency DC	
Driver included	ver included No	
Surge protection	-	
Inrush current	-	
Inrush time	-	
Power consumption tolerance	+/- 10%	
Beam angle	145°	
Beam spread	-	
Warranty period	3 years	
HS code	85395000	
Country of origin	People's Republic of China	

Spectral Output and Dimming Specifications

Dimmable	Yes	
Dimmable range	100% to 0%	
Colour temperature (K)	(K) 5000K, daylight dims to red	
CRI	>80	
Flicker index [Pst]	Exempt	
Stroboscopic effect [SVM]	Exempt	
Colour consistency [SDCM]	6	

Operating and Mechanical Specifications

Operating temperature	-10°C to 40°C / 14°F to 104°F	
Lumen maintenance L70B50 [h]	>50,000 hours	
Lens material	PC/PMMA	
Housing material	ing material PC/PMMA	
Diameter	16mm	
Height	-	
Length	1270mm (1900mm with cable)	
Width	-	
Mount / Adaptor	Steel wire using fixing clamps	
Connection	Connection Cables with snap-in connectors	
Control interface	terface PWM	
Product weight per piece	piece 0.41 Kg / 0.90 Lbs pc.	

Safety and Certifications

CE Mark	Yes
RoHS compliant	Yes
ANSI/UL	-
СВ	Yes
Flammability mark	V0
EU energy classification rating	Exempt
IEC protection class	Class III
IK impact rating	IK03
IP Code	IP69

Ordering Information

Description	SKU	Order code
TULEX-HO-PRO-120 Dim-to-Red	100000763	
TULEX-HO-PRO-120 Dim-to-Red (10 pcs)		929002100612

Contact us or learn more at:

www.once.lighting

ONCE Innovations Inc

3955 Annapolis Ave N, Suite 100 Plymouth, MN 55447 P +1(763) 297 9163

ONCE GmbH

Vechtaer Marsch 3 49377 Vechta, Germany P +49 (0)4441 8898-10

Email: once.info@signify.com



© 2022 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 12/2022 Data subject to change