

SILOX-BASIC-120-3000K




- Durable and quality tube lighting solution
- IP67 protection rating when paired with our ITF enclosures
- Easy retrofit solution with wide beam angle
- Sustainable tube light

Invest in the quality of your lighting system

The SILOX-BASIC-120-3000K offers total dimmability, high efficiency, energy savings, maximum durability, uniform light distribution and more. Pair with any of our ITF enclosures for a high protection grade (IP67), waterproof solution.

Dimensions



Visit our website for more information: www.once.lighting

Specifications and Ordering

SILOX-BASIC-120-3000K Specifications

Nominal power	22W
Luminous flux - human photopic	2700 lm
Luminous flux - poultry photopic	-
Initial LED luminaire efficacy	122 lm/W
Input voltage	230V
Input frequency	50/60 Hz
Driver included	Yes
Surge protection	-
Inrush current	-
Inrush time	-
Power consumption tolerance	+/- 10%
Power factor	0.95
Beam angle	145°
Warranty period	3 Years
HS code	85395000
Country of origin	People's Republic of China

Spectral Output and Dimming Specifications

Dimmable	Yes
Dimmable range	100% to 1%
Colour temperature (K)	3000K, warm white
CRI	>80
Flicker index [Pst]	0.01
Stroboscopic effect [SVM]	0.31
Colour consistency [SDCM]	6

Operating and Mechanical Specifications


Operating temperature	-10°C – 40°C / 14°F - 104°F
Lumen maintenance L70B50 [h]	>30,000 hours
Lens material	PC/PMMA
Housing material	Aluminum + PC
Diameter	25mm / 1 In (T8)
Height	-
Length	1200mm / 4 ft
Width	-
Mount / Adaptor	G13 rotatable base
Connection	T8-G13
Control interface	Trailing edge dimming
Product weight per piece	0.58 Kg / 1.27 Lbs pc.

Safety and Certifications

CE Mark	Yes
RoHS compliant	Yes
ANSI/UL	-
CB	-
Flammability mark	-
EU energy classification rating	E
IEC protection class	Class II
IK impact rating	Based on enclosure
IP Code	Based on enclosure

Ordering Information

Product name	SKU	12NC Order Code
SILOX-BASIC-120-3000K	1000000094	N/A



Contact us
or learn more at:
www.once.lighting

ONCE Innovations Inc
3955 Annapolis Ave N, Suite 100
Plymouth, MN 55447
P +1(763) 297 9163

ONCE GmbH
Vechtaer Marsch 3
49377 Vechta, Germany
P +49 (0)4441 8898-10

Email: once.info@signify.com

once
by **signify**

© 2022 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 12/2022 Data subject to change