

SILOX-BASIC-150-3000K




- Durable and quality tube lighting solution
- IP67 protection rating when paired with our ITF enclosures
- Easy retrofit solution with wide beam angle
- Sustainable tube light

Invest in the quality of your lighting system

The SILOX-BASIC-150-3000K offers total dimmability, high efficiency, energy savings, maximum durability, uniform light distribution and more. Pair with any of our ITF enclosures for a high protection grade (IP67), waterproof solution.

Dimensions



Visit our website for more information: www.once.lighting

Specifications and Ordering

SILOX-BASIC-150-3000K Specifications

	L	
Nominal power	24W	
Luminous flux - human photopic	2900 lm	
Luminous flux - poultry photopic	pic -	
Initial LED luminaire efficacy	120 lm/W	
Input voltage	230V	
Input frequency	50/60 Hz	
Driver included	Yes	
Surge protection	-	
Inrush current	-	
Inrush time	-	
Power consumption tolerance	+/- 10%	
Power factor	0.95	
Beam angle	145°	
Warranty period	3 Years	
HS code	85395000	
Country of origin	People's Republic of China	

Spectral Output and Dimming Specifications

Dimmable	Yes	
Dimmable range	100% to 1%	
Colour temperature (K)	3000K, warm white	
CRI	>80	
Flicker index [Pst]	0.01	
Stroboscopic effect [SVM]	0.39	
Colour consistency [SDCM]	6	

Operating and Mechanical Specifications


Operating temperature	-10°C – 40°C / 14°F - 104°F	
Lumen maintenance L70B50 [h]	>30,000 hours	
Lens material	PC/PMMA	
Housing material	Aluminum + PC	
Diameter	Diameter 25mm / 1 In (T8)	
Height	-	
Length	1500mm / 5 ft	
Width	-	
Mount / Adaptor	G13 rotatable base	
Connection	T8-G13	
Control interface	Control interface Trailing edge dimming	
Product weight per piece	0.7 Kg / 1.54 Lbs pc.	

Safety and Certifications

CE Mark	Yes	
RoHS compliant	Yes	
ANSI/UL	-	
СВ	-	
Flammability mark	-	
EU energy classification rating	E	
IEC protection class	Class II	
IK impact rating	Based on enclosure	
IP Code	Based on enclosure	

Ordering Information

Product name	SKU	12NC Order Code
SILOX-BASIC-150-3000K	100000099	N/A



Contact us or learn more at: www.once.lighting

ONCE Innovations Inc

3955 Annapolis Ave N, Suite 100 Plymouth, MN 55447 P +1(763) 297 9163

Email: once.info@signify.com

ONCE GmbH Vechtaer Marsch 3 49377 Vechta, Germany P +49 (0)4441 8898-10



© 2021 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Revised 2/2021 Data subject to change